

A/C NUMBER:

CHECK BEING PERFORMED: Cust

W/C NUMBER: 314M3101 (continued)

MECH: INSP:

(b) Route removed datacard to FOQA Analyst Office, HDQES/1.

XXXXX C. Install PCMCIA datacard.

(1) Open PCMCIA door on the front of the FDAU, 967-0212-002 FDAMS unit (Ref: AMM 31-31-22-2).

(2) Install the datacard into the left slot of the PCMCIA interface and close door on the front of the FDAU.

(3) Check to ensure the following:

(a) IN PROG LED light comes on after approximately 5 seconds.

(b) XFER COMP LED does not flash at approximately 1 second interval.

(c) XFER FAIL LED does not come on.

(4) If the XFER COMP LED flashes or if the XFER FAIL LED comes on, remove the PCMCIA datacard and install a serviceable card as per steps 1.B. and 1.C. (if available).

(5) If the XFER Comp LED continues to flash, or if the XFER FAIL LED still comes on, troubleshoot system (Ref: AMM 31-31-22-2).

XXXXX D. Return the aircraft to it's usual condition.

(1) Close E/E bay access door (117A).

(2) Remove aircraft electrical power, if required (Ref: AMM Task 24-22-00-860-811).

*****END OF WORKCARD*****