

**ATA AIRLINES, INC.**

FLIGHT COMPARTMENT CREW SEAT REMOVAL

PAGE 1 / 2

CHECK BEING PERFORMED: Custom

ZONES: 200  
A/C NUMBER:  
REV. DATE: 01/23/06  
FREQUENCY: 1C

W/C NUMBER: 321R2501      DATE:

MECH      INSP

---

MRB ITEM: 25-999A

1. Prepare for Captain Seat Removal

\_\_\_\_\_ XXXXX      A. Remove the Captain Crew Seat.

CAUTION: Place seatback in full upright position before moving seat to its fully aft and outboard position to prevent damage to circuit breaker panels.

(1) Move the seat to its fully aft and outboard position.

NOTE: PULL UP ON HORIZONTAL CONTROL HANDLE TO MOVE THE SEAT.

(2) Remove the stops from the front of the seat tracks.

(3) Move the seat forward until the rollers are free from the tracks.

(4) Lift the seat and remove it from the airplane.

\_\_\_\_\_ XXXXX 2. Attach a unserviceable tag to the seat and route to stores.

3. Prepare for First Officers Seat Removal

\_\_\_\_\_ XXXXX      A. Remove the First Officers Crew Seat.

CAUTION: Place seatback in full upright position before moving seat to its fully aft and outboard position to prevent damage to circuit breaker panels.

(1) Move the seat to its fully aft and outboard position.

NOTE: PULL UP ON HORIZONTAL CONTROL HANDLE TO MOVE THE SEAT.

(2) Remove the stops from the front of the seat tracks.

(3) Move the seat forward until the rollers are free from the tracks.

(4) Lift the seat and remove it from the airplane.

---

REVISION DATE: 01/23/06

ATA AIRLINES, INC. B737-800 FLEET

W/C #: 321R2501

DATE WORK CARD COMPLETE \_\_\_/\_\_\_/\_\_\_

FLIGHT COMPARTMENT CREW SEAT REMOVAL

PAGE:2 /2

A/C NUMBER:

CHECK BEING PERFORMED: Cust

W/C NUMBER: 321R2501 (continued)

MECH: INSP:

---

\_\_\_\_\_ XXXXX 4. Attach a unserviceable tag to the seat and route to stores.

\*\*\*\*\* END OF WORKCARD \*\*\*\*\*