

ATA AIRLINES, INC.

APPLY ANTI-CORR TO ENVIRONMENTAL CONTROL SYS COMP. LT AND RT

PAGE 1 / 1

CHECK BEING PERFORMED: Custom

ZONES: 117 118
A/C NUMBER:
REV. DATE: 04/09/99
FREQUENCY: D

W/C NUMBER: 510L5302
DATE:
W/O:
JAC CODE:



MFR P/N	DESCRIPTION	QTY
AV30	ANTI-CORROSION COMPOUND	A/R

TOOLS	DESCRIPTION	QTY
C-53-110-04		

PANELS

117AL	117CL
118CR	118ER

MECH INSP

| APPLY CORROSION INHIBITOR COMPOUND

|

| WARNING: ALWAYS USE A RESPIRATOR WHEN PERFORMING SPRAY

| APPLICATIONS. DO NOT APPLY CORROSION PREVENTATIVE

| TO FIBERGLASS DUCTS, HOT AIR DUCTS, OXYGEN SYSTEMS,

| BEARINGS, INSULATION, PLUMBING OR ANY AREA WHERE THE

| TEMPERATURE NORMALLY EXCEEDS 220 DEGREES F TO PREVENT

| FIRE HAZARD.

|

| CAUTION: SURFACES MUST BE CLEAN AND DRY PRIOR TO CORROSION

| PREVENTATIVE APPLICATIONS. TO PREVENT DAMAGE, DO NOT

| APPLY CORROSION PREVENTATIVE ON CABLES, WIRES, OR

| PLASTIC. DRAIN HOLES AND GAPS MUST BE CLEAR OF

| OBSTRUCTIONS.

|

| 1 APPLY SUITABLE APPROVED WATER DISPLACING/ANTI-CORROSION

| COMPOUND (AV30) TO INTERIOR OF HEAT EXCHANGER COMPARTMENTS.

_____ A L/H ENVIRONMENTAL CONTROL SYSTEM COMPARTMENT

_____ B R/H ENVIRONMENTAL CONTROL SYSTEM COMPARTMENT

*****End of Workcard*****