CHECK BEING PERFORMED: Custom

ZONES: 111 W/C NUMBER: 510L5304 DATE:
A/C NUMBER: W/O:
REV. DATE: 04/09/99 JAC CODE:
FREQUENCY: D

MFR P/N	DESCRIPTION	QTY
AV30	ANTI-CORROSION COMPOUND	A/R

TOOLS	DESCRIPTION	QTY
C-53-110-06		

PANELS
111A

MECH INSP

| APPLY CORROSION INHIBITOR COMPOUND

| WARNING: ALWAYS USE A RESPIRATOR WHEN PERFORMING SPRAY
| APPLICATIONS. DO NOT APPLY CORROSION PREVENTATIVE
| TO FIBERGLASS DUCTS, HOT AIR DUCTS, OXYGEN SYSTEMS,
| BEARINGS, INSULATION, PLUMBING OR ANY AREA WHERE THE
| TEMPERATURE NORMALLY EXCEEDS 220 DEGREES F TO PREVENT
| FIRE HAZARD.

| CAUTION: SURFACES MUST BE CLEAN AND DRY PRIOR TO CORROSION
| PREVENTATIVE APPLICATIONS. TO PREVENT DAMAGE, DO NOT
| APPLY CORROSION PREVENTATIVE ON CABLES, WIRES, OR
| PLASTIC. DRAIN HOLES AND GAPS MUST BE CLEAR OF
| OBSTRUCTIONS.

_____ _____ 1 APPLY SUITABLE APPROVED WATER DISPLACING/ANTI-CORROSION
| COMPOUND (AV30) TO FORWARD FACE OF FS 128 BULKHEAD.

********End of Workcard*********