


CHECK BEING PERFORMED: Custom

ZONES: 148 THRU 149
 A/C NUMBER:
 REV. DATE: 04/09/99
 FREQUENCY: D

W/C NUMBER: 510M2701
 DATE:
 W/O:
 JAC CODE:



MFR P/N	DESCRIPTION	QTY
1546995-101	SEALS	4
5738A	URALANE, FURBANE PRODUCTS CO., URALANE 5738A/B	A/R

REFERENCES

IPC 27-11-26

MECH INSP

- _____ XXXXX 1 REMOVE OUTPUT ARM FROM THE BOTTOM OF THE CAPT. & F/O'S AFT
 AILERON INPUT QUADRANT DRIVE SHAFT - ACCESS IN LH & RH WHEEL
 WELLS. REF. IPC 27-11-26 FIG. 1.
- _____ XXXXX 2 CHECK SHAFT ALIGNMENT WITH CUTOUT IN WHEEL WELL CEILING.
 CORRECT, IF ALIGNMENT CAUSES SIDELOAD WITH SEAL. REF. IPC
 27-11-26 FIG 1.
- _____ _____ 3 CLEAN AND INSPECT SEALS. REPLACE AS REQUIRED.
- | WARNING: URELANE 5738 CONTAINS TOLUNE DISOCYANETE DO NOT GET
 | IN EYES, ON SKIN OR ON CLOTHING. MIX IN AN EXHAUST
 | VENTILATED BOOTH. WEAR GLOVES WHILE MIXING AND
 |
 | APPLYING. IF GOTTEN ON THE SKIN OR IN THE EYES, IT
 | MAY CAUSE SEVERE IRRITATION. THE VAPOR IS HARMFUL,
 | IF INHALED. VAPORS MAY CAUSE ALLERGIC RESPIRATORY
 | AND SKIN REACTION. USE WITH ADEQUATE VENTILATION.
 | KEEP CONTAINER CLOSED WHEN NOT IS USE. WASH
 | THOROUGHLY, AFTER HANDLING. SEE MSDS FOR ADDITIONAL
 | DETAILS.
- _____ XXXXX 4 IF SHAFT MATING SEAL SLEEVE IS UNBONDED, REMOVE SHAFT AND BOND
 SLEEVE WITH URALANE 5738A, FURBANE PRODCUTS CO., URALANE
 5738A/B.
- _____ XXXXX 5 INSTALL SERVICEABLE SEALS IN CAPTS & F/O'S SHAFTS.
- _____ _____ 6 (R.I.I.) INSTALL CAPTS. & F/O'S OUTPUT ARMS.
- *****End of Workcard*****