

ATA AIRLINES, INC.

REPLACE FILTER AFT FUSELAGE DUCT ISOLN VALVE

PAGE 1 / 1

CHECK BEING PERFORMED: Custom

ZONES: 140  
A/C NUMBER:  
REV. DATE: 03/16/00  
FREQUENCY: 2C

W/C NUMBER: 515M3602  
DATE:  
W/O:  
JAC CODE:



MFR P/N	DESCRIPTION	QTY
2763397-101	FILTER ASSEMBLY (FOR POST S.B. ISOLATION VALVES)	A/R
2661058R015	PACKING (FOR POST S.B. ISOLATION VALVES)	A/R
2691075	FILTER (FOR PRE S.B. ISOLATION VALVES)	A/R
2-015S595-50	PACKING (FOR PRE S.B. ISOLATION VALVES)	A/R

TOOLS	DESCRIPTION	QTY
RAYTEK ST-4L	INFRARED THERMOMETER OR EQUIVALENT	1

PANELS

147AB

REFERENCES

MM36-14-01 515M3602

MECH INSP

---

\_\_\_\_\_ XXXXX 1 REPLACE AFT FUSELAGE DUCT ISOLATION VALVE FILTER (1 EA) AND 'O'  
RING (1 EA) PER MM36-14-01 PAGE 402.

NOTE: FILTER HAS FLAT TIP ON CLOSED END.

\_\_\_\_\_ 2 PERFORM A PNEUMATIC LEAK CHECK OF THE AFT FUSELAGE DUCT  
ISOLATION VALVE FILTER.

NOTE: IF AVAILABLE, USE OF AN INFRARED THERMOMETER (RAYTEK ST-4L OR EQUIVALENT) IS RECOMMENDED TO AID IN THE DETECTION OF HOT AIR LEAKS.

\*\*\*\*\*END OF WORKCARD\*\*\*\*\*