

ATA AIRLINES, INC.

CLEAN GALLEY OVEN EXHAUST DUCTS/INSP CONNECTORS/REPL/FAN AND CONTROL PAGE 1 / 1

CHECK BEING PERFORMED: Custom

ZONES: 200  
A/C NUMBER:  
REV. DATE: 03/16/00  
FREQUENCY: 2C

W/C NUMBER: 519M2104  
DATE:  
W/O:  
JAC CODE:



REFERENCES

MM21-24-08 MM21-24-15 519M2104

MECH INSP

\*\*\*\*\*  
\*WORK WITH GALLEY EXHAUST FILTER CHANGE SECTION OF THE B CHECK\*  
\*\*\*\*\*

\_\_\_\_\_ XXXXX 1 ON CABIN OVERHEAD CIRCUIT BREAKER PANEL, CB4, ZONE 254,  
OPEN AND TAG THE FOLLOWING CIRCUIT BREAKER:

GALLEY - EXHAUST - HEATER (N9)

\_\_\_\_\_ XXXXX 2 REMOVE CEILING GRILLE IN EACH GALLEY BY LOOSENING  
CAPTIVE SCREWS.

\_\_\_\_\_ XXXXX 3 REMOVE GALLEY EXHAUST FILTERS IAW MM 21-24-15.

XXXXX \_\_\_\_\_ 4 USE FLASHLIGHT TO ILLUMINATE INTERIOR OF ADAPTER, DUCTS, AND  
MUFFLERS AND VISUALLY CHECK FOR GREASE AND DIRT ACCUMULATION.  
IF ACCUMULATION IS EXCESSIVE, CLEAN DUCT IAW MM 21-24-08.

NOTE: IF GREASE AND DIRT ACCUMULATION IS EXCESSIVE IN UPPER  
PART OF VISIBLE DUCT, GENERATE NONROUTINE TO REMOVE  
DUCTING AND CLEAN AS REQUIRED UNTIL DUCT IS ACCEPTABLE.

\_\_\_\_\_ XXXXX 5 REINSTALL GALLEY EXHAUST FILTERS IAW MM 21-24-15.

\_\_\_\_\_ XXXXX 6 REINSTALL CEILING GRILLE IN EACH GALLEY BY SECURING  
CAPTIVE SCREWS.

\_\_\_\_\_ XXXXX 7 ON CABIN OVERHEAD CIRCUIT BREAKER PANEL, CB4, ZONE 254,  
CLOSE AND REMOVE TAG FROM THE FOLLOWING CIRCUIT BREAKER:

GALLEY - EXHAUST - HEATER (N9)

\*\*\*\*\*END OF WORKCARD\*\*\*\*\*