

ZONES: 200
A/C NUMBER:
REV. DATE: 06/23/06
FREQUENCY: 1C

W/C NUMBER: 522I2516
DATE:
W/O:
JAC CODE:



PANELS

NONE

522I2516

MECH INSP

XXXXX _____ 1. CHECK THE PORTABLE EMERGENCY FLASHLIGHT INSTALLATIONS. USE L-1011 EMERGENCY EQUIPMENT LOCATION PLACARD ON COCKPIT DOOR TO DETERMINE THE QUANTITY AND LOCATION OF PORTABLE EMERGENCY FLASHLIGHTS.

| NOTE: IF REQUIRED, MAKE A NON-ROUTINE CARD TO REPLACE BATTERIES AND TO OPERATIONALLY CHECK FLASHLIGHT FOR SERVICEABILITY. REPLACE FLASHLIGHT IN HOLDER WITH BREAK-AWAY COVER INSTALLED.

NOTE: EMERGENCY FLASHLIGHTS ARE INSTALLED AT EACH F/A STATION. THE LIGHT AUTOMATICALLY ILLUMINATES WHEN THE UNIT IS REMOVED FROM THE BRACKET AND CAN ONLY BE EXTINGUISHED BY RE-INSERTING THE UINIT IN THE BRACKET. THE UNIT IS SERVICEABLE ANY TIME THE COVER IS INTACT AND THE L.E.D IS FLASHING. IF THE TIME INTERVAL BETWEEN FLASHING IS MORE THAN 30 SECONDS, THE BATTERY MUST BE REPLACED. WHENEVER THE BATTERY IS REPLACED, THE BULB IS TO BE REPLACED ALSO AND THE FLASHLIGHT FUNCTIONALLY CHECKED.

*****END OF WORKCARD*****