

CHECK BEING PERFORMED: Custom

ZONES: 310
 A/C NUMBER:
 REV. DATE: 03/16/00
 FREQUENCY: H2

W/C NUMBER: 545M4901
 DATE:
 W/O:
 JAC CODE:



MFR P/N	DESCRIPTION	QTY
2763397-101	FILTER ASSEMBLY (FOR POST S.B. ISOLATION VALVES)	A/R
2661058R015	PACKING (FOR POST S.B. ISOLATION VALVES)	A/R
2691075	FILTER (FOR PRE S.B. ISOLATION VALVES)	A/R
2-015S595-50	PACKING (FOR PRE S.B. ISOLATION VALVES)	A/R

TOOLS	DESCRIPTION	QTY
RAYTEK ST-4L	INFRARED THERMOMETER OR EQUIVALENT	1

PANELS

317DL

REFERENCES

MM36-12-02 545M4901

MECH INSP

_____ XXXXX 1 REPLACE APU BLEED AIR S/O VALVE FILTER (1 EA) AND 'O' RING
 (1 EA) PER MM 36-12-02 PAGE 404

NOTE: FILTER HAS FLAT TIP ON CLOSED END

NOTE: SOME AIRCRAFT ARE CONFIGURED WITH A FILTER HOUSING AND
 2 "O" RINGS. PLUG FILTER CCN 3650156, MPN 2763397-101 &
 2 "O" RINGS CCN 9100376, MPN 2-015S595-50.
 (RETURN UNUSED PARTS TO STORES)

_____ 2 PERFORM PNEUMATIC LEAK CHECK OF THE APU BLEED AIR S/O VALVE
 FILTER.

NOTE: IF AVAILABLE, USE OF AN INFRARED THERMOMETER (RAYTEK
 ST-4L OR EQUIVALENT) IS RECOMMENDED TO AID IN THE
 DETECTION OF HOT AIR LEAKS.

*****END OF WORKCARD*****