

CHECK BEING PERFORMED: Custom

ZONES: 540 560  
 A/C NUMBER:  
 REV. DATE: 04/19/04  
 FREQUENCY: PCI

W/C NUMBER: 550L1201 DATE:  
 W/O:  
 JAC CODE:



MFR P/N	DESCRIPTION	QTY
BMS3-33	GREASE	AR
MIL-L-7870A	OIL	AR

REFERENCES

AMM 12-23-20 550L1201

MECH INSP

- 
- | 1. Lubricate all fittings on the LEFT HAND flap and vane  
 | installations per AMM 12-23-20.
  - \_\_\_\_\_ XXXXX No. 1 LH flap
  - \_\_\_\_\_ XXXXX No. 2 LH flap
  - \_\_\_\_\_ XXXXX No. 3 LH flap
  - \_\_\_\_\_ XXXXX No. 4 LH flap
  - | 2. Lubricate all fittings on the LEFT HAND spoiler installation  
 | per AMM 12-23-20.
  - \_\_\_\_\_ XXXXX No. 1 LH spoiler
  - \_\_\_\_\_ XXXXX No. 2 LH spoiler
  - \_\_\_\_\_ XXXXX No. 3 LH spoiler
  - \_\_\_\_\_ XXXXX No. 4 LH spoiler
  - \_\_\_\_\_ XXXXX No. 5 LH spoiler
  - \_\_\_\_\_ XXXXX No. 6 LH spoiler
  - | \_\_\_\_\_ XXXXX 3. Lubricate all LEFT HAND spoiler control linkage bell cranks  
 | per AMM 12-23-20.
  - | \_\_\_\_\_ XXXXX 4. Lubricate the LEFT WING slat actuators (7 locations) by  
 | wiping the small screw shaft clean with a dry rag and  
 | applying a light coat of MIL-L-7870A OIL. Lubricate the  
 | ball nut for the small screw.

\*\*\*\*\*END OF WORKCARD\*\*\*\*\*