

CHECK BEING PERFORMED: Custom

ZONES: 640 660  
 A/C NUMBER:  
 REV. DATE: 04/21/03  
 FREQUENCY: PCI

W/C NUMBER: 560L1201 DATE:  
 W/O:  
 JAC CODE:



| MFR P/N     | DESCRIPTION | QTY |
|-------------|-------------|-----|
| BMS3-33     | GREASE      | AR  |
| MIL-L-7870A | OIL         | AR  |

REFERENCES

MM 12-23-20 560L1201

MECH INSP

1 Lubricate all fittings on the RIGHT HAND flap and vane installations per MM 12-23-20.

\_\_\_\_\_ XXXXX No. 1 RH flap

\_\_\_\_\_ XXXXX No. 2 RH flap

\_\_\_\_\_ XXXXX No. 3 RH flap

\_\_\_\_\_ XXXXX No. 4 RH flap

2 Lubricate all fittings on the RIGHT HAND spoiler installation per MM 12-23-20.

\_\_\_\_\_ XXXXX No. 1 RH spoiler

\_\_\_\_\_ XXXXX No. 2 RH spoiler

\_\_\_\_\_ XXXXX No. 3 RH spoiler

\_\_\_\_\_ XXXXX No. 4 RH spoiler

\_\_\_\_\_ XXXXX No. 5 RH spoiler

\_\_\_\_\_ XXXXX No. 6 RH spoiler

\_\_\_\_\_ XXXXX 3 Lubricate all RIGHT HAND spoiler control linkage bell cranks per MM 12-23-20.

\_\_\_\_\_ XXXXX 4 Lubricate the RIGHT WING slat actuators (7 locations) by wiping the small screw shaft clean with a dry rag and applying a light coat of MIL-L-7870A OIL. Lubricate the ball nut for the small screw.

\*\*\*\*\*END OF WORKCARD\*\*\*\*\*