

ZONES: 123 212 215 216 W/C NUMBER: 711I2301 DATE:
 A/C NUMBER:
 REV. DATE: 06/07/07
 FREQUENCY: 1A

MECH INSP

MRB ITEM: 23-30-00-03

CABIN FIRE PROTECTION EQUIPMENT CHECK

Additional Zones: 225, 226, 231, 232, 241, 242, 251, 252, 261,
 262, 271, 272, 281, 282, 283, 291, 292

XXXXX 1. Inspect all portable fire extinguishers.

A. Make sure the pressure indicator is reading the correct pressure.

B. Make sure the fire extinguisher tamper seal is not broken.

C. Make sure the fire extinguisher is securely fastened.

2. Do an Operational Check of the Lavatory Smoke Test Circuit.

A. Supply electrical power.

B. Make sure applicable circuit breakers are closed.

C. Make sure the green power indicator light on the smoke detector face comes on.

D. Use an approved source to make smoke adjacent to each lavatory smoke detector.

E. Make sure these indications occur:

(1) The red alarm indicator light on the smoke detector face comes on.

(2) The alarm horn operates.

F. Push and hold the POWER/RESET switch for five seconds with a small screwdriver or other applicable tool.

G. Make sure the alarm horn stops and the red alarm indicator stays on.

H. Release the POWER/RESET switch.

I. Make sure the red alarm indicator stays on and the alarm horn stays off.

A/C NUMBER:

CHECK BEING PERFORMED: Cust

W/C NUMBER: 711I2301 (continued)

MECH: INSP:

- J. Remove the smoke from the lavatory.
- K. Make sure the red alarm indicator lamp goes off. Put the airplane back to its usual condition.
- L. Remove electrical power if it is not necessary.
- M. Record accomplishment of Step 2. for all lavatories.

- _____ XXXXX (1) Lav B
- _____ XXXXX (2) Lav C
- _____ XXXXX (3) Lav D
- _____ XXXXX (4) Lav E
- _____ XXXXX (5) Lav F
- _____ XXXXX (6) Lav H
- _____ XXXXX (7) Lav J

3. Inspect the lavatory trash container fire extinguisher fusible nozzles.

A. Make sure the nozzle is intact and does not indicate that the extinguisher has discharged.

4. Do a General Visual Inspection of the trash fire extinguisher and trash container area.

A. Make sure the fire extinguisher unit is secured properly.

B. Inspect Lavatory Trash Container Temperature Indicator (If Installed).

C. Make sure the fire extinguisher unit is not obstructed by anything.

D. Make sure no trash is behind the trash container and that the area is clean.

5. Record accomplishment of Steps 3. and 4. for all lavatories.

- _____ XXXXX A. Lav B

CABIN FIRE PROTECTION EQUIPMENT (INS,OPC)

A/C NUMBER:

CHECK BEING PERFORMED: Cust

W/C NUMBER: 711I2301 (continued)

MECH: INSP:

_____ XXXXX B. Lav C

_____ XXXXX C. Lav D

_____ XXXXX D. Lav E

_____ XXXXX E. Lav F

_____ XXXXX F. Lav H

_____ XXXXX G. Lav J

***** END OF WORKCARD *****