

ATA AIRLINES, INC.

AUTOMATIC AUTOPILOT DISENGAGE AURAL WARNING (AUTOLAND OPERATION

PAGE 1 / 1

CHECK BEING PERFORMED: Custom

ZONES: 112
A/C NUMBER:
REV. DATE: 06/07/07
FREQUENCY: 2A

W/C NUMBER: 714F2201 DATE:

PANELS

112AB

MECH INSP

MRB ITEM: 22-00-00-01

OPERATIONALLY CHECK AUTOMATIC AUTOPILOT DISENGAGE AURAL WARNING
(AUTOLAND OPERATION ONLY)

_____ XXXXX 1. Make sure electrical power is available.

_____ XXXXX 2. Close the following circuit breakers:

Circuit Breaker	Panel Location	Panel Area
ENG FIRE & OVSPD AURAL WARN	Overhead circuit breaker panel (Flight compartment)	BATTERY BUS
TO/LDG CAB PRESS AURAL WARN	Lower main circuit breaker panel (Flight engineer's station)	AC BUS 3
ALT ALERT HORIZ STAB AUTOPILOT AURAL WARN	Lower main circuit breaker panel (Flight engineer's station)	AC BUS 2

NOTE: The aural warning unit is installed in the avionics
compartment and is accessible through avionics equipment
door 112AB.

_____ XXXXX 3. Open avionics equipment door 112AB.

_____ XXXXX 4. Push to test switch, located on front of aural warning unit.

_____ XXXXX 5. Rotate knob to number 6 position, check for autopilot
disconnect warning wailer sound of 640 HZ every .210 seconds
on speakers.

_____ XXXXX 6. Release PUSH TO TEST switch.

_____ XXXXX 7. Close avionics compartment door 112AB.

***** END OF WORKCARD *****